



GLOBALUBE

TECHNICAL DATA SHEET

ATF Dexron III Synthetic

DESCRIPTION

Dexron III is a versatile automatic transmission fluid designed for various vehicles. Offering excellent frictional properties and thermal stability, it ensures smooth shifting and optimal performance. Its advanced formulation provides enhanced wear protection and fluid life, meeting the requirements for a wide range of automatic transmissions.

FEATURES AND ADVANTAGES

- Excellent wear protection
- Excellent seal protection
- Good shear stability
- High oxidation



PRODUCT PERFORMANCE CLAIMS

-GM DEXRON III F/ DEXRON III G, GM TYPE A SUFFIX A, ALLISON TES-389, MB-APPROVAL 236.9, MERCEDES BENZ MB 236.1/ 236.9, MAZDA M III FLUID, MAN 339 TYPE V1/V2, 339 TYPE Z1/Z2, FORD MERCON IV, FORD M2C-138CJ, VOITH H55.6335XX, VOLVO STD 1273.41(97341)

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Colour	-	VISUAL	Red
Density At 15°C	ASTM D4052	g/cm ³	0,844
Viscosity At 100 °C	ASTM D445	cSt	7,5
Viscosity At 40 °C	ASTM D445	cSt	34
Viscosity At -40 °C	ASTM D2983	cP	<20000
Viscosity Index	ASTM D2270	-	181
Flash Point, Open Cup	ASTM D92	°C	226
Pour Point	ASTM D97	°C	-51

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

