



GLOBALUBE

TECHNICAL DATA SHEET

CVTF NS3 Fully Synthetic

DESCRIPTION

CVTF NS3 (Continuous Variable Transmission Fluid, Nissan NS-3) is a transmission fluid specifically formulated for Nissan vehicles equipped with CVTs. It ensures smooth and efficient power transfer, enhances belt and pulley durability, and provides excellent lubrication. CVTF NS3 meets Nissan's stringent requirements for optimal CVT performance and longevity.

FEATURES AND ADVANTAGES

- Excellent wear protection
- Excellent seal protection
- Good shear stability
- High oxidation



PRODUCT PERFORMANCE CLAIMS

-PROTON CVT, PERODUA CVT, VOLVO 4959, TOYOTA CVTF TC,FE,HONDA HMMF,HCF 2,NISSAN NS1, NS2,NS3,MITSUBISHI J4/JJ1,SUBARU ICVT,FORD MERCON C, MINI COOPER EZL 799

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Colour	-	VISUAL	Red
Density At 15°C	ASTM D4052	g/ml	0,845
Viscosity At 100 °C	ASTM D445	cSt	7,2
Viscosity At 40 °C	ASTM D445	cSt	35
Viscosity At -40 °C	ASTM D2983	cP	15,000
Viscosity Index	ASTM D2270	-	181
Flash Point, Open Cup	ASTM D92	°C	205
Pour Point	ASTM D97	°C	-46

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

