



**GLOBALUBE**

## TECHNICAL DATA SHEET

# DOT 3 Brake & Clutch Fluid

### DESCRIPTION

DOT 3 Brake & Clutch Fluid is a high-quality hydraulic fluid designed for braking and clutch systems. With a glycol ether base, it offers reliable lubrication and corrosion protection. Its high boiling point helps prevent vapor lock, ensuring consistent brake and clutch performance for safe and efficient vehicle operation.

### FEATURES AND ADVANTAGES

- Excellent brake response
- Enquiring good braking performance
- Excellent thermal stability



### PRODUCT PERFORMANCE CLAIMS

- FMVSS 116 DOT 3 SAE J1703
- JISK 2233 MS119
- HI-TEMPERATURE 400 °F

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Appearance	VISUAL	-	Red Liquid
pH	SAE J1703	pH	7-11
ERBP (Equilibrium Reflux Boiling Point)	SAE J1703	°C	Min 240
Density @20 °C	IP 160	g/ml	1.05
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	min 145

### HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

