



Globalube, a prominent force in lubricants, is dedicated to excellence and innovation. Globalube, as a key player in the lubricant industry, is devoted to excellence and ingenuity. As a leading brand, we prioritize top-tier quality, ensuring our lubricants not only meet but surpass industry benchmarks, enhancing machinery performance worldwide. What sets us apart is our commitment to sustainability — we embrace eco-friendly practices, making a positive impact on the environment. With Globalube, you're not just getting lubricants; you're gaining a dependable partner committed to delivering cutting-edge technology, ensuring your machinery runs smoothly, efficiently, and responsibly. Welcome to the future of lubrication — welcome to Globalube.

OUR MISSION

Globalube's mission is to lead the lubricants industry with exceptional products and services. Committed to excellence, innovation, and sustainability, we strive to optimize machinery performance globally. Our customer-centric approach tailors solutions to individual needs, ensuring unparalleled service. At the core of our mission is a dedication to crafting eco-friendly practices for a greener future. Join us in redefining lubrication success.

OUR VISION

Globalube is dedicated to customer satisfaction, tailoring lubrication solutions to individual needs. Our commitment to excellence, innovation, and sustainability optimizes machinery performance worldwide. We prioritize crafting eco-friendly practices for a greener future, inviting you to join us in reshaping the definition of lubrication success.





SAE **OW20**

API SP/CF



SAE 0W30

API SP/CF



SAE 5W20

API SP/CF



SAE 5W30

API SP/CF



SAE 5W40

API SP/CF



SAE 10W30

API SP/CF





SAE 10W30

SPECIFICATION: ILSAC GF-6A, API SP/CK-4 ACEA C3/B4, ACEA C3



SAE 5W20

API SP/CK-4



SAE 5W30

API SP/CK-4



SAE 10W40

API SP/CK-4





ATF DEXRON III

SYNTHETIC BLENDED



ATF SP III

SYNTHETIC BLENDED



ATF TYPE IV

SYNTHETIC BLENDED



ATF DEXRON VI

FULLY SYNTHETIC



CVTF NS3

FULLY SYNTHETIC





SAE 20W50 API SM/CI-4

SAE 10W40

API SM/CI-4



SAE 40

EXCEEDS API SF/CF



SAE **75W90**

SAE **80W90**

EP 90

EP 140

SYNTHETIC BLENDED

API GL-5 LSD



BRAKE & CLUTCH FLUID

mannanan ma



DOT 3
HI-TEMPERATURE 400°F



DOT 4

HI-TEMPERATURE 450°F

POWER STEERING FLUID



PSF-S

SUITABLE FOR ALL KIND OF VEHICLES

COOLANT



COOLANT

CONCENTRATED

HYDRAULIC FLUID



AWS 68
HIGH-QUALITY



