



GLOBALUBE

TECHNICAL DATA SHEET

Power Steering Fluid

DESCRIPTION

Power Steering Fluid is a specialized hydraulic fluid that ensures smooth and efficient operation of power steering systems. Formulated to withstand high temperatures and reduce wear, it facilitates easy steering, minimizes friction, and extends the life of power steering components for optimal vehicle performance.

FEATURES AND ADVANTAGES

- Maintains performance in high and low temperature conditions
- Helps stop squeals and leaks under severe conditions
- Protects against oxidation, corrosion, and water.



PRODUCT PERFORMANCE CLAIMS

- BMW 81229407758
- DAIRRLER CHRYSLER MS5931
- VOLVO 1161529
- VW TL 52146
- FORD WSS-M2C204-A
- GM 9905010
- HONDA PSF

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Colour	VISUAL	-	Red
Density At 15°C	ASTM D4052	g/cm ³	0.844
Viscosity At 100 °C	ASTM D445	cSt	7,5
Viscosity At 40 °C	ASTM D445	cSt	34
Viscosity At -40 °C	ASTM D2983	cP	20000 max
Viscosity Index	ASTM D2270	-	181
Flash Point, Open Cup	ASTM D92	°C	226
Pour Point	ASTM D97	°C	-51

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

