



GLOBALUBE

TECHNICAL DATA SHEET

SAE 0W30 Fully Synthetic

DESCRIPTION

SAE 0W-30 fully synthetic motor oil is a high-performance lubricant designed for modern engines. With a low-viscosity formula, it ensures efficient cold starts, reduces friction, and provides excellent wear protection. Meeting industry standards, this fully synthetic oil offers optimal engine performance and longevity.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Sae Grade	-	-	0W-30
Density @ 15°C	ASTM D4052	g/cm ³	0.846
Viscosity At 100 °C	ASTM D445	cSt	9.5
Viscosity At 40 °C	ASTM D445	cSt	49.7
Viscosity At -35 °C	ASTM D5293	cP	5714
Viscosity Index	ASTM D2270	-	178
Open Cup Flash Point	ASTM D92	°C	218
Freezing Point	ASTM D97	°C	-45

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

