



GLOBALUBE

TECHNICAL DATA SHEET

SAE 10W30 Fully Synthetic

DESCRIPTION

SAE 10W30 Fully is a premium motor oil with a viscosity grade of 10W30, providing excellent engine lubrication and reliable cold start capabilities. The "Fully" indicates a fully synthetic formulation, delivering superior protection, stability, and performance in various temperatures and driving conditions.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

-API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
-ACEA A3/B4-12, ACEA C3-10
-MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
-MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Sae Grade	-	-	10W-30
Density At 15°C	ASTM D4052	g/cm ³	0.850
Kinematic Viscosity At 100 °C	ASTM D445	cSt	10.5
Kinematic Viscosity At 40 °C	ASTM D445	cSt	64
CCS Viscosity At -25 °C	ASTM D5293	cP	<7,000
Viscosity Index	ASTM D2270	-	154
Flash Point, Open Cup	ASTM D92	°C	240
Pour Point	ASTM D97	°C	-36
T.B.N.	ASTM D2896	mg KOH/g	7.6
Shearing Inj. Bosch: Vis 100 °C (30cy)	CEC L-14-93	cSt	9.8
Noack Volatility, 1h At 250 °C	CEC L-40-93	% in weight	<15
HTHS, Viscosity At 150 °C	CEC L-36-90	cP	>2,9

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

