



GLOBALUBE

TECHNICAL DATA SHEET

SAE 10W30 Mineral

DESCRIPTION

SAE 10W30 mineral oil is a traditional lubricant derived from refined crude oil. With a balanced viscosity (10W30), it offers reliable engine protection in diverse temperatures. Ideal for older engines, this mineral oil provides essential lubrication, safeguarding against wear and maintaining engine performance.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

- API SM/CI-4
- ACEA A3/B3-04,A3/B4-04
- MB 229.1
- VW505.01/VW502.00

| PARAMETER | METHOD | UNIT | TYPICAL RESULT |
|-------------------------------|------------|--------------------|----------------|
| Density At 15°C, Relative | ASTM D4052 | g/ml | 0.864 |
| Viscosity , Kinematics 100 °C | ASTM D445 | mm ² /s | 10.5 |
| Viscosity , Kinematics 40 °C | ASTM D445 | mm ² /s | 68 |
| Viscosity Index | ASTM D2270 | None | 150 |
| Viscosity ,CCS -25 °C (10W) | ASTM D5293 | mPa.s (cP) | 5000 |
| Total Base Number ,TBN | ASTM D2896 | Mg KOH/g | 9.8 |

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

