



GLOBALUBE

TECHNICAL DATA SHEET

SAE 10W30 Semi Synthetic

DESCRIPTION

SAE 10W30 semi-synthetic oil is a versatile lubricant suitable for various climates. Its viscosity, indicated by the "10W30" rating, provides optimal engine protection, ensuring smooth operation and improved fuel efficiency. The semi-synthetic formula blends synthetic and conventional oils for enhanced performance and engine durability.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Sae Grade	-	-	10W-30
Density At 15°C	ASTM D4052	g/ml	0.8686
Viscosity At 100 °C	ASTM D445	cSt	12
Viscosity At 40 °C	ASTM D445	cSt	82
Viscosity At -25 °C	ASTM D5293	cP	<7,000
Viscosity Index	ASTM D2270	-	141
Flash Point, Open Cup	ASTM D92	°C	232
Pour Point	ASTM D97	°C	-45
T.B.N.	ASTM D2896	mg KOH/g	8,9
Bosch Injector Shearing:	CEC L-14-A-93	cSt	>9.3
Sulphated Ashes	ASTM D874	% weight	0.9

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

