



GLOBALUBE

TECHNICAL DATA SHEET

SAE 10W40 Mineral

DESCRIPTION

SAE 10W40 mineral oil is a classic lubricant crafted from refined crude oil. Tailored for dependable engine protection, especially in warmer climates, it maintains essential viscosity (10W40) for smooth operation. Ideal for older engines, this mineral oil safeguards against wear and sustains engine longevity.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

-API SM/CI-4
-ACEA A3/B3-04,A3/B4-04
-MB 229.1
-VW505.01/VW502.00

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density At 15 °C	ASTM D4052	g/ml	0,867
Viscosity at 100 °C	ASTM D445	cSt	14,2
Viscosity At 40°C	ASTM D445	cSt	95
Viscosity Index	ASTM D2270	-	160
Pour Point	ASTM D97	°C	-42
Noack Volatility,1hr at 250 °C	DIN 51581	%	-
TBN	ASTM D2896	mg KOH/g	7
Bosch Injector Shearing:	CEC L-14-93	cSt	12,5

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

