



GLOBALUBE

TECHNICAL DATA SHEET

SAE 10W40 Semi Synthetic

DESCRIPTION

SAE 10W40 semi-synthetic oil is a premium lubricant designed for versatile engine performance. Balancing synthetic and conventional oils, it ensures reliable protection in various conditions. The viscosity rating (10W40) guarantees optimal flow, enhancing engine efficiency and durability for a wide range of applications.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15 °C , Relative	ASTM D4052	g/ml	0.85
Viscosity , Kinematic 100 °C	ASTM D445	mm ² /s	13.0
Viscosity ,CCS -30 °C (5W)	ASTM D5293	mPa.s (cP)	5800
Viscosity , Kinematic 40 °C	ASTM D445	mm ² /s	75
Viscosity Index	ASTM D2270	None	174
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	202
Ash Sulphated	ASTM D874	% wt	0.8

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

