



GLOBALUBE

TECHNICAL DATA SHEET

SAE 5W40 Fully Synthetic

DESCRIPTION

SAE 5W40 Fully is a high-performance motor oil with a viscosity grade of 5W40, ensuring superior engine lubrication and cold weather start-up. The "Fully" designates a fully synthetic composition, offering advanced protection, stability, and optimal performance across diverse temperatures and driving conditions.

FEATURES AND ADVANTAGES

- Improve fuel economy
- Extends oil lifespan
- Reduce emission



PRODUCT PERFORMANCE CLAIMS

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Sae Grade	-	-	5W-40
Density At 15°C	ASTM D4052	g/ml	0.850
Viscosity At 100 °C	ASTM D445	cSt	14.1
Viscosity At 40 °C	ASTM D445	cSt	87
Viscosity At -30 °C	ASTM D5293	cP	6600 max
Viscosity Index	ASTM D2270	°C	170
Flash Point, Open Cup	ASTM D92	°C	215 min
Pour Point	ASTM D97	°C	-36
T.B.N.	ASTM D2896	mg KOH/g	10.5
Sulphated Ash	ASTM D874	% weight	1.5 max
Bosch Injector Shearing : Viscosity At 100 °C After Shearing	CEC-L-14-93	cSt	12.5 min
Noack Volatility 1h At 250 °C	CEC-L-40-93	cSt	11.5% max

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

