



GLOBALUBE

TECHNICAL DATA SHEET

ATF SP III Synthetic

DESCRIPTION

ATF SP III is a specialized automatic transmission fluid designed for specific applications. Providing superior frictional properties and thermal stability, it ensures smooth and precise shifting. Formulated for compatibility with certain Hyundai and Kia transmissions, ATF SP III offers reliable wear protection and optimal performance in these systems.

FEATURES AND ADVANTAGES

- Excellent wear protection
- Excellent seal protection
- Good shear stability
- High oxidation



PRODUCT PERFORMANCE CLAIMS

-PROTON SP III, PERODUA ATF D3-SP, NISSAN MATIC D, J, KIA SP III, JWS 3314, SUBARU ATF-HP, MERCEDES BENZ 236.01;09;10 ATF 3403M-115, ISUZU G052990 (09M), MITSUBISHI ATF SP III, HYUNDAI SP III, JWS 3313

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Sae Viscosity Grade	-	-	SP III
Density At 15°C	ASTM D4052	g/cm ³	0,855
Flash Point	ASTM D92	°C	180
Pour Point	ASTM D97	°C	-45
Kinematic Viscosity At 40 °C	ASTM D445	cSt	38
Viscosity At 100 °C	ASTM D445	cSt	7.5
Viscosity Index	ASTM D2270	-	169

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

